全自動給袋機
Automatic bag feeder



致力於為經銷商提供專業配套解決方案成為您專業配套的首選
包裝機一站式服務，助您輕鬆拓展市場



電腦多頭組合秤
Multi-head Weigher



液體灌裝機
Liquid fillre



螺杆粉劑頭
Screw powder head



工作平台
Working platform



檢重秤
Checkweigher



金屬檢測器
Metal detector



大傾角提升機
Large angle hoist



Z型提升機
Z-type hoist



碗式提升機
Bowl hoist

200A
Automatic bag feeder
全自動給袋機











機器型號 Machine model	200A
設備材料 Equipment and materials	304不鏽鋼（與食品接觸部分） 304 stainless steel(part in contact with food)
氣動元件 Pneumatic components	德國費斯托FESTO (標准件)、 臺灣亞德客（非標件） FESTO,Germany(standard parts),adek,Taiwan(non-standard parts)
驅動方式 Driving mode	機械傳動(凸輪齒輪杠杆全機械模式) Mechanical transmission(can gear lever full mechanical mode)
計量方式 Measurement method	收縮杯計量、碗投下料、組合秤等（可配選） Shrinkage cup metering,bowl feeding,combined scale,etc.(optional)
適用物料 Applicable materials	蜜餞糕點、瓜子、花生、堅果炒類、膨化類、小袋裝大袋產品等（不抽真空） Candied pastries melon seeds,peanuts,fried nuts,expandep products,products in small bags,etc.(no vacuum pumping)
工作流程 Workflow	①上袋 ②打碼 ③開袋、撐袋 ④下料一/下震（選配） ⑤下料二 ⑥預留 ⑦封口一 ⑧封口二、整形 ①Bag loading②coding ③bag opening and bag supporting ④blanking i/down shock (optional)⑤blanking ii⑥reservation ⑦sealing i ⑧sealing ii,shaping
封口方式 Sealing method	根據產品可兩道封口，確保封口美觀牢固 According to the product,two seals can be used to ensure that seal is beautiful and firm
包裝速度 Packaging speed	30包~60包/分鐘（具體由產品自身及充量決定） 30 packs~ 60 packs/min(depending on the product itself and the charge)
包裝袋材料 Packing bag materials	自立袋、拉鏈袋、四邊封袋、三邊封袋、紙袋（表面覆紙）等 Self standing bag,zipper bag,four side sealed bag,three side sealed bag,paper bag (surface coatedwith paper),etc
包裝袋規格 Bag se pcification	寬60mm*200mm 長100mm*350mm W60mm*200mm L100mm*350mm
總功率 Total power	主機功率≈6KW Main engine powe ≈6KW
耗氣量 Gas consumption	0.6m³/min
驅動電源 Driving power supply	三相380V 50HZ(非國標三相380V 60HZ) Three phase 380V 50HZ(non-national standard three-phase 380V 60HZ)
機器外形 Machine shape	1921mm*1916mm*1460mm (L*W*H)(不含提升機) 1921mm*1916mm*1460mm（L*W*H)(excluding hoist)
機器稱重 Machine weight	1.5T (主機) 1.5T(Host)
使用環境 Use environment	室溫10℃~40℃ 30~90% RH,無露、無腐蝕性氣體、無灰塵等其他惡劣環境 Room temperature 10℃~40℃,30~90%RH,no dew,corrosive gas,dust and other harsh environments

260A
Automatic bag feeder
全自動給袋機











機器型號 Machine model	260A
設備材料 Equipment and materials	304不鏽鋼（與食品接觸部分） 304 stainless steel(part in contact with food)
氣動元件 Pneumatic components	德國費斯托FESTO (標准件)、 臺灣亞德客（非標件） FESTO,Germany(standard parts),adek,Taiwan(non-standard parts)
驅動方式 Driving mode	機械傳動(凸輪齒輪杠杆全機械模式) Mechanical transmission(can gear lever full mechanical mode)
計量方式 Measurement method	收縮杯計量、人工投料、全自動螺杆計量、鹵蛋自動下料計量、組合秤等（可配選） Shrinkage cup metering,manual feeding,fu ii-automatic screw metering,automatic fee ing metering of marinated eggs,combined scale,etc.(optional)
適用物料 Applicable materials	蜜餞糕點、瓜子、花生、堅果炒類、膨化類、小袋裝大袋產品等（不抽真空） Candied pastries melon seeds,peanuts,fried nuts,expandep products,products in small bags,etc.(no vacuum pumping)
工作流程 Workflow	①上袋 ②打碼 ③開袋、撐袋 ④下料一/下震（選配） ⑤下料二 ⑥預留 ⑦封口一 ⑧封口二、整形 ①Bag loading②coding③bag opening and bag supporting ④blanking i/down shock(optional) ⑤blanking ii ⑥reservation ⑦sealing i ⑧sealing ii 、Shaping
封口方式 Sealing method	根據產品可兩道封口，確保封口美觀牢固 According to the product,two seals can be usd to ensure that the seal is beautiful and firm
包裝速度 Packaging speed	30包~60包/分鐘（具體由產品自身及充量決定） 30 packs~ 60 packs/ min(depending on the product itself and the charge)
包裝袋材料 Packing bag materials	自立袋、拉鏈袋、四邊封袋、三邊封袋、紙袋（表面覆紙）等 Self standing bag,zipper bag,four side sealed bag,three side sealed bag,paper bag (surface coated with paper),etc
包裝袋規格 Bag se pcification	寬130mm*260mm 長100mm*400mm W 130mm*260mm L100mm*400mm
總功率 Total power	主機功率≈6KW Main engine powe ≈6KW
耗氣量 Gas consumption	0.6m³/min
驅動電源 Driving power supply	三相380V 50HZ(非國標三相380V 60HZ) Three phase 380V 50HZ(non-national standard three-phase 380V 60HZ)
機器外形 Machine shape	1921mm*1916mm*1460mm (L*W*H)(不含提升機) 1921mm*1916mm*1460mm（L*W*H)(excluding hoist)
機器稱重 Machine weight	1.8T (主機) 1.8T(Host)
使用環境 Use environment	室溫10℃~40℃ 30~90% RH,無露、無腐蝕性氣體、無灰塵等其他惡劣環境 Room temperature 10℃~40℃,30~90%RH,no dew,corrosive gas,dust and other harsh environments

300A
Automatic bag feeder
全自動給袋機











機器型號 Machine model	300A
設備材料 Equipment and materials	304不鏽鋼（與食品接觸部分） 304 stainless steel(part in contact with food)
氣動元件 Pneumatic components	德國費斯托FESTO、 日本SMC (標准件)、 臺灣亞德客（非標件） FESTO In germany,SMC in japan(standard parts),adek,Taiwan(non-standard parts)
驅動方式 Driving mode	機械傳動(凸輪齒輪杠杆全機械模式) Mechanical transmission(can gear lever full mechanical mode)
計量方式 Measurement method	碗投下料、組合秤等（可配選） bowl feeding,combined scale,etc.(optional)
適用物料 Applicable materials	大片毛肚、堅果炒類、大紅棗、膨化類、小袋裝大袋產品等（不抽真空） Candied pastries melon seeds,peanuts,fried nuts,expandep products,products in small bags,etc.(no vacuum pumping)
工作流程 Workflow	①上袋 ②打碼 ③開袋、撐袋 ④下料一/下震（選配） ⑤下料二 ⑥預留 ⑦封口一 ⑧封口二、整形 ①Bag loading②coding ③bag opening and bag supporting ④blanking i/down shock (optional)⑤blanking ii⑥reservation ⑦sealing i ⑧sealing ii,shaping
封口方式 Sealing method	根據產品可兩道封口，確保封口美觀牢固 According to the product,two seals can be used to ensure that seal is beautiful and firm
包裝速度 Packaging speed	20包~40包/分鐘（具體由產品自身及充量決定） 20 packs~40 packs/ min(depending on the product itself and the charge)
包裝袋材料 Packing bag materials	自立袋、拉鏈袋、四邊封袋、三邊封袋、紙袋（表面覆紙）等 Self standing bag,zipper bag,four side sealed bag,three side sealed bag,paper bag (surface coatedwith paper),etc
包裝袋規格 Bag se pcification	寬180mm*300mm 長200mm*450mm W 180mm*300mm L200mm*450mm
總功率 Total power	主機功率≈5KW Main engine powe ≈5KW
耗氣量 Gas consumption	0.6m³/min
驅動電源 Driving power supply	三相380V 50HZ(非國標三相380V 60HZ) Three phase 380V 50HZ(non-national standard three-phase 380V 60HZ)
機器外形 Machine shape	2045mm*2133mm*1517mm (L*W*H) (不含提升機) 2045mm*2133mm*1517mm（L*W*H)(excluding hoist)
機器稱重 Machine weight	2T (主機) 2T(Host)
使用環境 Use environment	室溫10℃~40℃ 30~90% RH,無露、無腐蝕性氣體、無灰塵等其他惡劣環境 Room temperature 10℃~40℃,30~90%RH,no dew,corrosive gas,dust and other harsh environments

金華瑞科技有限公司
Jin Huaw